



General Specifications/规格:

1. Panel Size/板的尺寸: 21" x 24", 20" x 22.7", 16" x 18"
2. Panel Thickness/板的厚度: 0.025mm ~ 3.0mm

TS91028-2 FIFO BUFFER BF15

TS91028-2 functions as a First In First Out Buffer of PCB as thin as 0.025mm at tact time of 10 panels per minute. It can be integrated with Conveyor Units, Inner Layer Exposure Automation Systems or Lamination Automation Systems.

Additional Alignment Conveyors with Contactless Centering are optional especially with thin panels.

Machine Specifications

Model	TS91028-2
Panel Size	21" x 24", 20" x 22.7", 16" x 18"
Panel Thickness	0.025mm ~ 3.0mm
C/V Pass Line	950mm ± 30mm
Tact Speed	10 panel/min (Max)
Storage Capacity	15 panels
Electrical Connection	3 phase, 230v+N, 50Hz, 1KVA
Air Supply	6 Bar
Machine Weight	800 Kg per unit
Machine Size	850mm(L)x1600mm(W)x2150mm(H)

Options

Safety Feature	Swing door with safety sensor ; Sliding door with safety sensor ; Curtain sensor
Conveyor Type	Flat belt 3x30mm+2x130mm ; Flat belt 5x30mm ; Roller Φ60mm

Your Ideal Partner in Automated Engineering Equipment
Email: transystem@pacific.net.sg