




Front View
正视图



Flip Over Unit
翻转机构



PCB Picker
PCB 提取臂



Tray
托盘



V Magazine
V型托盘



PCB Exchange
PCB交换

General Specifications/规格:

1. Panel Size/板的尺寸: 18" x 24" (Min) ~ 21" x 24"(Max)
2. Panel Thickness/板的厚度: 3.2mm (Max); 0.025mm (Min)

TS71039

TS71039 functions as Loader and Unloader of PCB as thin as 0.025mm at exchange time at AOI of about 4 seconds for PCB inspection. It accepts V magazine and trays on trolleys at about 795mm height and interfaces to AOI at pass height of about 950mm. The Contactless Centering Belt Conveyor senses the edges of the PWB and the Conveyor moves to compensate the difference during referencing before placing onto the AOI and before placing onto the output V-Magazine or Tray. Optional items are PCB referencing unit, PCB stopper, Interleave magazine and conveyor configuration.

该设备能作为厚度为0.025mm的PCB的收放板机，PCB自动检测的交换时间大约是4秒。该设备接受高度大约是795mm的V型托盘或平托盘，它可以连接到高度为950mm的AOI装置。在PWB进入AOI之前和输出到V型托盘或平托盘之前，要通过无接触中心定位装置。当装置感应到PWB的边缘，通过传送带移动以抵消误差。可选的项目是PCB定位装置、PCB停止装置、插入纸托盘和传送机构的形状。