



### Machine Specifications

Model	TS72503-2
Plate Size	457 x 609 (Min) ~ 558 x 660 (Max)
Plate Thickness	2mil-62mil
Tact Speed	4.5~5 panel/min
Magazine Pass Line	825 ± 30mm
Conveyor Pass Line	950 ± 30mm
Loading Position	One V-type magazine
Electrical Connection	AC415V+N+PE, 3 phase, 50Hz,9KW
Air Supply	5 Bar
Machine Size	1560mm(L) x 1150mm(W) x 2150mm(H)

### Options

Safety Feature	Swing door with safety sensor	Sliding door with safety sensor	Curtain sensor	
Picker Pad	Φ33mm	Φ20mm	Φ18mm	Φ14mm
Picker Type	2 Fixed rows+1 Manual adjust row		2 Fixed rows+3 Position pneumatic row	
	2 Fixed rows+1 Motor adjust row		2 Fixed rows	Custom design
Conveyor Type	Roller Φ40mm			
PCB Stopper	Single position		Double position	
PCB Centering	Centering fingers		Contactless Centering	
Separation	Single poulder	Double poulder	Triple poulder	Vibration
PCB Edge Referencing	Diverter with hard stop			
Thickness Checker	Double piece sensor			

**Your Ideal Partner in Automated Engineering Equipment**  
**Email: [transystem@pacific.net.sg](mailto:transystem@pacific.net.sg)**